

Pokost Iniany NS

Linseed oil varnish without siccative

Date of edition: 05.05.2009

Date of updating: 05.10.2018

DESCRIPTION

Linseed oil varnish without siccative is made of thickened linseed oil without drying accelerating additives. It has a very high penetration ability, as well as high elasticity. It protects the painted objects against harmful action of water and influence of unfavourable weather conditions.

APPLICATIONS

Linseed oil varnish is intended for impregnation of wood, wood-based materials, plasters or other porous materials. It can be used for indoor and outdoor applications for protection from humidity.

PROPERTIES

Appearance	clear liquid; without impurities	
Flow time , Ford cub ϕ 4mm, 20°C, PN-C-81701 method A	20-26	s
Density , 20°C PN-82/C81551 method B	0,93± 0,02	g/cm ³
Colour PN-84/C-04534/02, max.	40	mg I ₂ /100 cm ³

GUARANTEE PERIOD

12 months from the production date.

TRANSPORT & STORAGE

Transport and store in tightly closed containers at 0°C to +30°C.

PACKAGING

Pallet container 1000 l, tank truck, or other packaging agreed with the customer.

*It is not the COA parameter.

The data are based on our current knowledge and are intended to provide general notes on our products, their technical data and applications. They do not relieve processors from carrying out their own investigations and tests. They also cannot be regarded as a guarantee in the legal sense.

Pokost Iniany NS

Linseed oil varnish without siccative

SAFETY & HEALTH, FIRE SAFETY INFORMATION

Prolonged contact or inhalation of varnish vapours can irritate eyes, skin and respiratory system. Therefore, during work wear protective clothing, use gloves and goggles. Ensure adequate ventilation.

First aid measures:

If swallowed, do not induce vomiting, give a lot of water to drink and seek medical advice . Irrigate the irritated eyes copiously with water for at least 15 minutes. Seek medical help. Wash the contaminated skin with water and soap. In the case of respiratory system irritation, bring the exposed victim into the fresh air.

Linseed oil varnish is a flammable product.

Fire extinguishing measures: carbon dioxide, alcohol resistant foam extinguisher.

The data are based on our current knowledge and are intended to provide general notes on our products, their technical data and applications. They do not relieve processors from carrying out their own investigations and tests. They also cannot be regarded as a guarantee in the legal sense.