Pigment paste for paints and plasters



BETAPRINT® Red 10112



Date od issue: 10.12.2009 Update: 10.12.2022

Colour Index P.R.101

Chemical characteristics of the pigment: Iron Oxide Red **CN Code:** 3206 49 70

Physical nature of the product : Fluid

Product description

BETAPRINT® Red 10112 is water based dispersion of pigment, dispersants and other auxiliary means.

Product features

pH PN-EN ISO 787-9	7 – 10
Density approx. (g/cm³) PN-EN ISO 2811-1	1,86±3%
Viscosity (mPa·s) Brookfield R4/50, 20±0,5°C, PN-EN ISO 3219	500-5000
Pigment light fastness	
Full shade	8
Tint shade 1/3	8
Pigment weathering fastness	
Full shade	5
Tint shade 1/3	5

Applications

Emulsion paints, enamels, silicate, silicone and acrylic plasters.

Warranty period

12 months from the date of manufacture.

Transport and storage

Store and transport in tightly sealed containers made of polyethylene or in metal barrels secured from inside with lacquer coat at temperatures between 5 and 40°C.

The data are based on our current knowledge and are intended to provide general notes on our products, their technical data and applications. They do not relieve processors from carrying out their own investigations and tests. They also cannot be regarded as a guarantee in the legal sense.