

Product Data Sheet

Pigment paste for paints and plasters



BETAPRINT® Red 1223 (BETAPRINT® Czerwony 1223)



Date of issue: 10.12.2009

Update: 16.09.2016

Colour Index P.R. 122

Chemical characteristics of the pigment:	Quinacridone	CN Code	3204 17 00
Physical nature of the product :	Fluid		

Product description

Betaprint Red 1223 is water based dispersion of pigment, dispersants and other auxiliary means. Due to its good weathering fastness it is appropriate for applications with outdoor and indoor paints.

Product features

pH PN-EN ISO 787-9	8-10
Density* (g/cm ³) PN-EN ISO 2811-1	1,10±5%
Viscosity (mPa·s) Brookfield, 20±0,5°C, PN-EN ISO 3219	3000-6000
Pigment concentration approx. (%)	30
Colour accuracy, ΔE, max.	1
Pigment light fastness	
Full shade	7-8
Tint shade 1/3	7-8
Pigment weathering fastness	
Full shade	4-5
Tint shade 1/3	4-5

Applications

Emulsion paints, enamels, silicate, silicone and acrylic plasters.

Warranty period

12 months from the date of manufacture.

Transport and storage

Store and transport at temperatures between 5 and 40°C in tightly sealed containers made of polyethylene or in metal barrels secured from inside with lacquer coat.

The data are based on our current knowledge and are intended to provide general notes on our products, their technical data and applications. They do not relieve processors from carrying out their own investigations and tests. They also cannot be regarded as a guarantee in the legal sense.