

Product Data Sheet

Pigment paste for paints and plasters



BETAPRINT® Blue 1532 (BETAPRINT® Niebieski 1532)



Date of issue: 10.12.2009

Update: 14.05.2015

Colour Index P.B.15:3

Chemical characteristics of the pigment: Phthalocyanine β **CAS No.:** 147-14-8
Physical nature of the product : Fluid

Product description

BETAPRINT® Blue 1532 is water based dispersion of pigment, dispersants and other auxiliary means. Due to its good weathering fastness it is appropriate for applications with outdoor and indoor paints.

Product features

pH PN-EN ISO 787-9	7 – 9
Density* (g/cm³) PN-EN ISO 2811-1	1,250±2,4%
Viscosity (mPa·s) Brookfield R4/50, 20±0,5°C, PN-EN ISO 3219	600-1500
Pigment concentration approx. (%)	35
Colour accuracy, ΔE, max.	1
Pigment light fastness	
Full shade	8
Tint shade 1/3	8
Pigment weathering fastness	
Full shade	5
Tint shade 1/3	5

Intended use

Emulsion paints, enamels, s, silicone and acrylic plasters.

Warranty period

12 months from the date of manufacture.

Transport and storage

Store and transport in tightly sealed containers made of polyethylene or in metal barrels secured from inside with lacquer coat at temperatures between 5 and 40°C.

*It is not the COA parameter.

The data are based on our current knowledge and are intended to provide general notes on our products, their technical data and applications. They do not relieve processors from carrying out their own investigations and tests. They also cannot be regarded as a guarantee in the legal sense.